

Tabela bazowych anten dookólnych

Producent						Parametry					Cena [zł]
Diamond	Lafayette	Comet	Procom	Grauta	FiberGain	Pasma [MHz]	Typ [λ] lub Rodzaj	Zysk [dBi]	Długość [mm]	Netto	Brutto
X-30N						144/430	1/2, 2x5/8	3,0/5,5	1300	170,73	210
X-50N						144/430	6/8, 2x5/8	4,5/7,2	1700	191,06	235
X-200N						144/430	2x5/8, 4x5/8	6,0/8,0	2500	268,29	330
X-300N						144/430	2x5/8, 5x5/8	6,5/9,0	3100	308,94	380
	MA-200					144/430	2x5/8, 6x5/8	6,5/9,5	2550	211,38	260
	MA-2000					144/430	2x5/8, 6x5/8	6,5/9,5	2550	211,38	260
	MV-2000					50/144/430	1/4, 2x5/8, 5x5/8	2,15/6,2/8,4	2550	284,55	350
X-510N						144/430	3x5/8, 8x5/8	8,3/11,7	5200	402,44	495
	X-5000N					144/430/1200	6/8, 3x5/8, 7x5/8	4,5/8,3/11,7	1800	292,68	360
		GP-9N				144/430	3x5/8, 8x5/8	8,5/11,9	5000	601,63	740
X-5000N						144/430/1200	6/8, 3x5/8, 7x5/8	4,5/8,3/11,7	1800	560,98	690
X-700HN						144/430	4x5/8, 11x5/8	9,3/13,0	7200	1284,55	1580
X-7000N						144/430/1200	3x5/8, 8x5/8, 14x5/8	8,3/11,7/13,7	5000	691,06	850
	VH-50					136~174	1x5/8	4,5	1750	178,86	220
BC-100						134~174	1x5/8	4,5	1700	235,77	290
BC-200						430~490	3X5/8	6,5	1700	252,03	310
					BC-100	134~184	1x5/8	4,5	1500	178,86	220
					F-22	144~174	2x5/8	6,7	3000	227,64	280
					F-23	144~174	3x5/8	7,8	4000	239,84	295
F-22						144~174	2x7/8	6,7	3200	357,72	440
				KAD VHF		136~174 *	Collinear	5,65	2700	544,72	670
				KAD MAX		136~174 *	3x5/8	7,15	4400	626,02	770
			CXL-2-3LW/L			146~154	Collinear	5	2800	1097,56	1350
			CXL-2-3LW/H			166~175	Collinear	5	2800	1504,07	1850
	UH-50					400~480	2x5/8	7,5	1500	227,64	280
			CXL 70-1/h			420 ~ 470	1/2	2	560	398,37	490
				KAD UHF		396~510 *	Collinear	7,65	2700	544,72	670
			CXL-3-1LW			118~136	1/2, lotnicza	2	1500	886,99	1091
		AB-380				108~140, 220~400	lotnicza	2,15	1170	414,63	510
	MFV-110V					156 ~ 163	morska	4,5	1200	77,24	95
	MFV-240V					156 ~ 162	morska	6,5	2400	113,82	140

* Anteny sprzedawane są w różnych grupach ze względu na zakres częstotliwości. Dokładne wykazy grup znajdują Państwo na naszej stronie internetowej.

- anteny sugerowane do zastosowań profesjonalnych